



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

Issued: 06/08/2019
Ref: WFS/ Watson Fuels/ ULP / 01
Version: 01

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 PRODUCT IDENTIFIER

Chemical Identification: ULP
Other names: Unleaded Petrol, Gasoline

1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Relevant Identified Uses: Fuel for use in petrol engine vehicles designed to run on unleaded petrol (spark ignition engines).

Uses advised against: This product is not to be used as a solvent or cleaning agent, for lighting or brightening fires, or as a skin cleanser. NOT for aviation use.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Supplier: Watson Fuels
Address: Lindum House
Causeway End
Brinkworth
Chippenham
Wiltshire
SN15 5DN
UK
Tel: +44 1666 510 345
Email: hse@watsonfuels.co.uk

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone (24hr): +44 (0) 333 333 9957 (24/7)

SECTION 2. HAZARDS IDENTIFICATION

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

ACCORDING TO REGULATION (EC) No. 1272/2008 (CLP)

Classification Flam. Liq. 1; H224
Asp. Tox. 1; H304
Skin Irrit. 2; H315
Muta. 1B H340
Carc. 1B; H350
Repr. 2; H361df
STOT SE 3; H336
Aquatic Chronic 2; H411

Please see section 16 for full hazard statements

SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

2.2 LABEL ELEMENTS

ACCORDING TO REGULATION (EC) No. 1272/2008 (CLP)



Hazard pictogram(s):

Signal Word: Danger

Hazard statement(s):

- H224: Extremely flammable liquid and vapour.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H340: May cause genetic defects.
- H350: May cause cancer
- H361df: Suspected of damaging fertility. Suspected of damaging the unborn child
- H336: May cause drowsiness or dizziness.
- H410: Very toxic to aquatic life with long lasting effects.

Precautionary statement(s):

- P102: Keep out of reach of children.
- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P273 Avoid release to the environment
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- P331: Do NOT induce vomiting.
- P405: Store locked up.
- P501: Dispose of contents/container in accordance with local / national regulations.

Supplementary Hazard Information (EU): None

Hazard Determining Component(s): Gasoline; Petroleum naphtha fraction, co-processed (catalytic cracking) with renewable hydrocarbons of plant and/or animal origin.

2.3 OTHER HAZARDS:

The product does not meet the criteria for PBT or vPvB substances.
Electrostatic charge may be generated during pumping and other operations. Sparks may ignite liquid and vapour.
Vapours may form explosive mixtures with air.
Spillages make surfaces slippery.



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2 MIXTURES

Mixture manufactured from gasoline. Paraffinic, olefinic and aromatic hydrocarbons mixture, with a number of carbons in a rank of C4 - C12 and a boiling interval from 25 to 210°C. Max. sulphur: 10 mg/kg.

Chemical Name	CAS No., EINECS No., Index No.	REACH Registration Number	Concentration	Classification
Gasoline A complex combination of hydrocarbons consisting primarily of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons having carbon numbers predominantly greater than C3 and boiling in the range of 30°C to 260°C	86290-81-5, 289-220-8, 649-378-00-4	01- 2119471335- 39-xxxx	60 – 100	Flam. Liq. 1; H224 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Muta 1B: H340 Carc. 1B: H350 Repr. 2: H361df STOT SE 3: H336 Aquatic Chronic 2: H411
Petroleum naphtha fraction, co-processed (catalytic cracking) with renewable hydrocarbons of plant and/or animal origin	-, [701-149-0] -	01- 2120737196- 51-0000	0 - < 30	Flam. Liq. 1; H224 Asp. Tox. 1; H304 Skin Irrit. 2; H315 Muta. 1B H340 Carc. 1B: H350 Repr. 2: H361df STOT SE 3: H336 STOT RE 2: H373 Aquatic Chronic 2: H411
Ethanol	64-17-5, 200-578-6, 603-002-00-5	01- 2119457610- 43-xxxx	0 - < 5	Flam. Liq. 2; H225
Methanol	67-56-1, 200-659-6, 603-001-00-X	01- 2119433307- 44-xxxx	0 - < 3	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H311 Acute Tox. 3; H331 STOT SE 1; H370 Optic nerve, CNS

Please see section 16 for full hazard statements.

SECTION 4. FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES

General Advice:

Obtain medical attention if symptoms do not resolve. Show this safety data sheet to the doctor in attendance.

Inhalation:

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If casualty is unconscious and not breathing, or if



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

	breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If the casualty is unconscious and breathing, place in the recovery position with the head below level of the torso. Immediately obtain specialist medical assessment and treatment for the casualty.
Ingestion:	Obtain medical attention immediately. Do not wait for symptoms to develop. Do not induce vomiting. Do not give anything by mouth because of risk of material entering the lungs and causing lung damage. If person is drowsy or unconscious and vomiting, place on left side with head down. If possible, do not leave unattended and observe closely for adequacy of breathing.
Eye contact:	Remove contact lenses if present and easy to do. Wash eyes immediately with plenty of water, making sure to rinse under eyelids. If symptoms persist, obtain medical attention.
Skin contact:	Drench contaminated clothing with water before removing to avoid risk of sparks from static electricity. Take off contaminated clothing and wash it before reuse. Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. For minor thermal burns, cool the burn. Hold the burned area under cold running water for at least five minutes, or until the pain subsides. Body hypothermia must be avoided. Accidental high-pressure injection through the skin requires immediate medical attention. Do not wait for symptoms to develop.
Protection of first aiders:	No action shall be taken involving any personal risk or without suitable training. Ensure adequate ventilation. Spillages make surface slippery.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Aspiration into the lungs may occur directly or following ingestion. This may cause chemical pneumonitis which may be fatal. If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. Ingestion may also cause gastrointestinal irritation, nausea, diarrhoea and vomiting.

Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in drowsiness, dizziness, light headedness, headache, disorientation, fatigue, nausea and loss of coordination. The onset of respiratory symptoms may be delayed for several hours after exposure.

Eye contact may cause redness and transient pain.

Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. Prolonged or repeated skin contact may cause dry skin and irritation and defatting of the skin.

May cause cancer. May cause genetic defects. Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

In case of accident or if you feel unwell, seek medical advice immediately. If swallowed, patient should be monitored for signs of breathing difficulty as effects of aspiration may be delayed for up to 48 hours. If breathing is laboured, oxygen should be administered by qualified personnel.



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

SECTION 5. FIREFIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

Suitable: Alcohol resistant foam, inert gas, sand, earth, CO₂ or dry powder.

Not suitable: Do not use a direct water jet. Do not use foam and water simultaneously, as water destroys the foam. Water spray may be inefficient for fighting fire.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Flammable liquid and vapour: Vapour may form explosive mixture with air. Vapour is heavier than air and may accumulate in confined spaces. Vapours may travel considerable distances to ignition sources where they can ignite, flash back or explode. The product will float on surface water and can reignite. Containers exposed to heat may burst due to increase in pressure.

Hazardous thermal decomposition products:

Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke), carbon monoxide, oxides of sulphur, hydrogen sulphide and unidentified organic and inorganic compounds.

5.3 ADVICE FOR FIRE-FIGHTERS

A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Move undamaged containers from fire area if this can be done safely. Keep fire exposed containers cool by spraying with water. Do not allow to enter drains, sewers or watercourses. Isolate the area.

Firefighting measures: Isolate the source of the combustible product. If fire cannot be extinguished, allow it to die out in a controlled manner. Use water to cool down equipment and items exposed to fire.

Additional advice: Keep adjacent containers cool by spraying with water. If possible, remove containers from the danger zone. If the fire cannot be extinguished, the only course of action is to evacuate immediately.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

6.1.1 For non-emergency personnel:

Alert emergency personnel. Keep unnecessary personnel away.

Flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use explosion-proof electrical, ventilating and lighting equipment.

Caution – spillage area may be slippery.



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

Keep upwind. Ensure adequate ventilation. Avoid inhalation of vapours. Avoid contact with skin and eyes. Wear suitable personal protective equipment. Wear appropriate respirator when ventilation is inadequate. (See Section 8). Stop the leak if safe to do so.

6.1.2 For emergency responders:

Flammable. Spillages of liquid product will create a fire hazard and may form an explosive atmosphere. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Use explosion-proof electrical, ventilating and lighting equipment.

Keep unnecessary personnel away. Keep upwind. Ensure adequate ventilation. Avoid inhalation of vapours. Avoid contact with skin and eyes. Wear suitable personal protective equipment:

Small spillages: normal antistatic working clothes are usually adequate.

Large spillages: full body suit of chemically resistant and thermal resistant material should be used. Work gloves providing adequate chemical resistance, specifically to aromatic hydrocarbons. Note: gloves made of PVA are not water-resistant and are not suitable for emergency use. Safety helmet, antistatic non-skid safety shoes or boots. Goggles and/or face shield, if splashes or contact with eyes is possible or anticipated.

Respiratory protection: a half or full-face respirator with filter(s) for organic vapours or, preferably, a Self-Contained Breathing Apparatus (SCBA) can be used according to the extent of spill and predictable amount of exposure. If the situation cannot be completely assessed, or if an oxygen deficiency is possible, only SCBA should be used.

6.2 ENVIRONMENTAL PRECAUTIONS

Collect spillage. Stop the leak if it is safe to do so. Do not allow to enter drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be alerted to the Environment Agency or other appropriate regulatory body. In case of soil contamination, remove contaminated soil and treat in accordance with local regulations. Inform the relevant authorities if the product has caused environmental pollution.

6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

6.3.1 For containment:

Stop the leak if it is safe to do so. Contain the spillage with sand, earth or any suitable non-combustible adsorbent material.

6.3.2 For cleaning up:

Use sand, earth or any suitable non-combustible adsorbent material to adsorb spillages. Using non-sparking tools, transfer the contaminated adsorbent material into a container for disposal.

For spillages on water, remove using appropriate methods such as skimming, booms or adsorbents. For spillages onto soil, remove contaminated soil for remediation or disposal in accordance with local regulations.

Waste containers used should be plastic-lined sealable drums. Containers should be sealed before being disposed of via an authorised waste disposal contractor.

6.4 REFERENCE TO OTHER SECTIONS

For personal protective equipment, see Section 8. For disposal, see Section 13.



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

SECTION 7. HANDLING AND STORAGE
--

7.1 PRECAUTIONS FOR SAFE HANDLING

Extremely flammable. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Use only outdoors or in a well-ventilated area. Provide adequate ventilation, including local extraction, to ensure occupational exposure limits are not exceeded. Avoid breathing vapours/spray. Avoid contact with skin and eyes. Wear suitable personal protective equipment (See Section 8). Open container slowly. The vapor is heavier than air and may create an explosive mixture of vapor and air. Beware of accumulation in confined spaces and low-lying areas. Do not enter confined spaces such as tanks or pits without following proper entry procedures.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Avoid release to the environment.

Do not eat, drink or smoke in the vicinity of the product. Wash thoroughly after handling. Take off contaminated clothing and wash it before reuse. Contaminated clothing should be thoroughly cleaned or disposed of as hazardous waste.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Keep away from heat and sources of ignition. Keep away from direct sunlight. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Empty containers retain product residue and can be hazardous. Keep away from oxidising agents, reducing agents. This product must never be stored in buildings occupied by people. Drums and small containers should be stored in well-ventilated areas, flameproof cabinets or stores. Keep in a bunded area with a sealed floor to provide containment against spillage. Seek specialist advice for the design, construction and operation of bulk storage facilities.

7.3 SPECIFIC END USE(S)

Refer to the end uses as identified section 1.2.



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Workplace exposure limits

Source: EH40/2005, 3rd Ed., 2018, Suppliers' recommendations and American Conference of Governmental Industrial Hygienists (ACGIH).

Substance	Type	LTEL (8 hr TWA)		STEL (15 min)		Comments
		ppm	mg/m ³	ppm	mg/m ³	
Gasoline	ACGIH	300		500	-	
Gasoline	Supplier's recommendations	0.5 ⁽¹⁾		2.5 ⁽¹⁾	-	Sk
Petroleum naphtha fraction, co-processed (catalytic cracking) with renewable hydrocarbons of plant and/or animal origin	Supplier's recommendations		450		1100	Sk
Toluene ⁽²⁾	UK, EH40	50	191	100	384	Sk
n-Hexane ⁽²⁾	UK, EH40	20	72	-	-	
Benzene ⁽²⁾	UK, EH40	1	3.25	-	-	Carc, Sk
Ethylbenzene ⁽²⁾	UK, EH40	100	441	125	552	Sk
Xylene, mixed isomers ⁽²⁾	UK, EH40	50	220	100	441	Sk, BMGV
Ethanol	UK, EH40	1000	1920			
Methanol	UK, EH40	200	266	250	333	Sk

⁽¹⁾ (with > 0.1% benzene)

⁽²⁾ Components of gasoline.

Sk Can be absorbed through the skin

Carc Capable of causing cancer and/or heritable genetic damage.

BMGV Biological monitoring guidance values

Biological Monitoring Guidance Values

Substance	BMGV	Sampling Time
Xylene, o-, m-, p- or mixed isomers	650 mmol methyl hippuric acid/mol creatinine in urine	Post shift

DNELs (Workers)

Hazard via inhalation route:

	Gasoline	Petroleum naphtha fraction, co-processed (catalytic cracking) with renewable hydrocarbons of plant and/or animal origin	Ethanol	Methanol
Systemic, Chronic	No hazard identified	No hazard identified	950 mg/m ³	260 mg/m ³
Systemic, Acute	1300 mg/m ³	1300 mg/m ³	No hazard identified	260 mg/m ³
Local, Chronic	840 mg/m ³	840 mg/m ³	No hazard identified	260 mg/m ³
Local, Acute	1100 mg/m ³	1100 mg/m ³	No hazard identified	260 mg/m ³



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

Hazard via dermal route:

	Gasoline	Petroleum naphtha fraction, co-processed (catalytic cracking) with renewable hydrocarbons of plant and/or animal origin	Ethanol	Methanol
Systemic, Chronic	No hazard identified	No hazard identified	343 mg/kg bw/day	40 mg/kg bw/day
Systemic, Acute	No hazard identified	No hazard identified	No hazard identified	40 mg/kg bw/day
Local, Chronic	High hazard	Medium hazard	No hazard identified	No hazard identified
Local, Acute	Low hazard	Medium hazard	No hazard identified	No hazard identified

DNELs (Consumers)

Hazard via inhalation route:

	Gasoline	Petroleum naphtha fraction, co-processed (catalytic cracking) with renewable hydrocarbons of plant and/or animal origin	Ethanol	Methanol
Systemic, Chronic	No hazard identified	No hazard identified	114 mg/m ³	50 mg/m ³
Systemic, Acute	1200 mg/m ³	1200 mg/m ³	No hazard identified	50 mg/m ³
Local, Chronic	180 mg/m ³	180 mg/m ³	No hazard identified	50 mg/m ³
Local, Acute	640 mg/m ³	640 mg/m ³	No hazard identified	50 mg/m ³

Hazard via dermal route:

	Gasoline	Petroleum naphtha fraction, co-processed (catalytic cracking) with renewable hydrocarbons of plant and/or animal origin	Ethanol	Methanol
Systemic, Chronic	No hazard identified	No hazard identified	206 mg/kg bw/day	8 mg/kg bw/day
Systemic, Acute	No hazard identified	No hazard identified	No hazard identified	8 mg/kg bw/day
Local, Chronic	High hazard	Medium hazard	No hazard identified	No hazard identified
Local, Acute	Low hazard	Medium hazard	No hazard identified	No hazard identified

Hazard via oral route:

	Gasoline	Petroleum naphtha fraction, co-processed (catalytic cracking) with renewable hydrocarbons of plant and/or animal origin	Ethanol	Methanol
Systemic, Chronic	No hazard identified	No hazard identified	87 mg/kg bw/day	8 mg/kg bw/day
Systemic, Acute	No hazard identified	No hazard identified	No hazard identified	8 mg/kg bw/day

PNEC related information:

Gasoline and Petroleum naphtha fraction, co-processed (catalytic cracking) with renewable hydrocarbons of plant and/or animal origin: Products comprise mostly of hydrocarbons with a complex, unknown or variable composition. Conventional methods of deriving PNECs are not appropriate and it is not possible to identify a single representative PNEC for such substances.



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

PNEC	Ethanol	Methanol
Freshwater	0.96 mg/L	20.8 mg/L
Freshwater (intermittent releases)	2.75 mg/L	1 540 mg/L
Marine water	0.79 mg/L	2.08 mg/L
STP	580 mg/L	100 mg/L
Sediment (freshwater)	3.6 mg/kg sediment dw	77 mg/kg sediment dw
Sediment (marine water)	2.9 mg/kg sediment dw	7.7 mg/kg sediment dw
Air	No hazard identified	No hazard identified
Soil	0.63 mg/kg soil dw	100 mg/kg soil dw
Oral (Predators, secondary poisoning)	0.38 g/kg food	No potential for bioaccumulation

8.2 EXPOSURE CONTROLS

8.2.1 Appropriate engineering controls

Provide adequate ventilation to ensure that occupational exposure limits are not exceeded. Local extraction may be required. Eye wash and quick-drench shower facilities should be available in the work area. Contaminated clothing and shoes should be thoroughly washed before reuse.

8.2.2 Individual protection measures, such as personal protective equipment

Eye protection: Goggles or safety glasses with side shields giving complete protection to eyes. (EN 166). Depending on conditions of use, close-fitting eye protection and a face shield may be necessary.

Skin protection: Long sleeve protective clothing. Nitrile, neoprene or PVC apron. Rubber boots.

Hand protection: Chemical-resistant gloves. (EN 374). Suitable glove material: nitrile, neoprene or PVC (breakthrough time > 240 minutes). Breakthrough times for gloves vary depending on, e.g. chemical resistance, material thickness, frequency and duration of contact. Selection should also consider other usage requirements, e.g. dexterity, heat resistance, other chemical substances handled. Always seek advice from glove suppliers. Contaminated gloves should be replaced.

Respiratory protection: Where airborne levels below the exposure limits cannot be maintained, wear an air-purifying respirator (EN 140) with a Type A/P2 filter or better suitable for organic gases and vapours with a boiling point above 65°C. (EN 14387).

Thermal hazards Wear suitable temperature resistant gloves and protective clothing if the product is heated.

8.2.3 Environmental exposure controls:

Avoid release to the environment. Inform environmental manager of all incidents involving this product. Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an Occupational Exposure Limit and adequacy of exposure controls. For some substances, biological monitoring may also be appropriate. Information on suitable methods is available on request.



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Liquid (Clear and bright, pale yellow coloured)
Odour:	Characteristic - gasoline
Odour threshold:	No data available.
pH:	Not applicable.
Melting/freezing point:	No data available
Initial boiling point and boiling range:	22 – 210 °C
Flash point:	- 40 °C (ASTM D56)
Evaporation rate:	10 – 11 (nBuAc = 1)
Flammability (solid; gas):	Not applicable
Upper/lower flammability or explosive limits:	Lower: 1.3 % Upper: 7.6 %
Vapour pressure:	45-100 kPa @20°C
Vapour density:	> 1 (Air = 1)
Relative density:	0.720-0.775 @15°C
Solubility(ies):	Solubility in water: 0.01g/L
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	450 °C
Decomposition temperature:	Not available.
Viscosity:	0.5-1.5 mm ² /s @ 20°C
Explosive properties:	Not explosive. Vapour may form explosive mixture in air.
Oxidising properties:	Not oxidising.

9.2 OTHER INFORMATION

Pour Point: No data available

SECTION 10. STABILITY AND REACTIVITY

10.1 REACTIVITY

Reacts with oxidising agents.

10.2 CHEMICAL STABILITY

The product is stable under normal use conditions

10.3 POSSIBILITY OF HAZARDOUS REACTIONS:

No hazardous reactions expected during normal conditions.

10.4 CONDITIONS TO AVOID

Avoid high temperatures. Keep away from all sources of ignition, hot surfaces, direct sunlight. Prevent accumulation of vapours. Contact with strong oxidizing agents e.g. chlorates and ammonium nitrate.



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

10.5 INCOMPATIBLE MATERIALS:

Strong oxidising agents and strong reducing agents.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

Combustion may liberate toxic fumes: Carbon monoxide, carbon dioxide, various hydrocarbons, nitrogen oxides, sulphur oxides.

SECTION 11. TOXICOLOGICAL INFORMATION

Note: All information in this section is for Fuels, diesel. Information given is based on product data, knowledge of the components and the toxicology of similar products.

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

Acute Oral Toxicity:	Not classified. Based on the available data the classification criteria are not met.
Acute Dermal Toxicity:	Not classified. Based on the available data the classification criteria are not met.
Acute Inhalation Toxicity:	Not classified. Based on the available data the classification criteria are not met.
Skin Corrosion/Irritation:	Causes skin irritation.
Serious Eye Damage/Irritation:	Not classified. Based on the available data the classification criteria are not met.
Skin sensitisation:	Not classified. Based on the available data the classification criteria are not met.
Respiratory sensitisation:	Not classified. Based on the available data the classification criteria are not met.
Germ Cell Mutagenicity:	May cause genetic defects.
Carcinogenicity:	May cause cancer.
Reproductive Toxicity:	Suspected of damaging fertility and the unborn child
Specific target organ toxicity – single exposure:	May cause drowsiness or dizziness. (CNS by inhalation) High concentrations of vapour may cause central nervous system (CNS) depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.
Specific target organ toxicity - repeated exposure:	Not classified. Based on the available data the classification criteria are not met.
Aspiration hazard:	May be fatal if swallowed and enters airways. Risk of aspiration into lungs resulting in chemical pneumonia.

Information on likely routes of exposure

Inhalation	High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.
Skin contact	Causes skin irritation. Prolonged or repeated skin contact may cause dry skin and



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

Eye contact irritation and defatting of the skin.
May cause slight eye irritation, redness, transient pain, watering.

Ingestion May be fatal if swallowed and enters airways. Risk of aspiration into lungs resulting in chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics:

Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. Prolonged or repeated skin contact may cause dry skin and irritation and defatting of the skin.

Eye contact may cause slight irritation, watering, redness and pain.

Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in drowsiness, dizziness, light headedness, headache, disorientation, fatigue, nausea and loss of coordination. The onset of respiratory symptoms may be delayed for several hours after exposure. Ingestion may cause irritation of the mouth and digestive tract. If swallowed, aspiration into lungs may result in chemical pneumonia.

Chronic Effects:

May cause genetic defects. May cause cancer. Suspected of damaging fertility and the unborn child

Other information:

High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

SECTION 12. ECOLOGICAL INFORMATION

12.1 TOXICITY

Very toxic to aquatic life with long lasting effects.

	Gasoline	Petroleum naphtha fraction, co-processed (catalytic cracking) with renewable hydrocarbons of plant and/or animal origin	Ethanol	Methanol
Short-term toxicity to fish	LL50 (96 hours) 8.2 - 10 mg/L (WAF)	LL50 11 mg/L (estimated)	LC50 11200 mg/L	LC50 15400 mg/L
Long-term toxicity to fish	EL50 (21 days) 10 mg/L	LL50 0.92 mg/L (estimate)	EC10 250 mg/L	NOEC: 450 mg/L
Short-term toxicity to aquatic invertebrates	EL50 (48 hours) 4.5 mg/L (WAF)	EC50 7.6 mg/	EC50 857 mg/L, (marine water invertebrates)	LC50 >10000 mg/L
Long-term toxicity to aquatic invertebrates	NOELR (21 days) 2.6 mg/L	LL50 1.59 mg/L (estimate)	NOEC 79 mg/L, (marine water invertebrates)	NOEC 208 mg/L
Short-term toxicity to aquatic algae	EL50 (72h) 3.1 mg/L (WAF)	EC50 3.1 mg/L	EC50 275 mg/L	EC50 22000 mg/L

12.2 PERSISTENCE/DEGRADABILITY:

Gasoline is a hydrocarbon UVCB, so tests are not usually appropriate. Gasoline has the potential to be inherently biodegradable. Ethanol and Methanol are readily biodegradable.



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

12.3 BIOACCUMULATION POTENTIAL:

Gasoline is a hydrocarbon UVCB, so tests are not usually appropriate. Ethanol and methanol have a low potential for bioaccumulation (log Kow < 3).

12.4 MOBILITY IN SOIL:

Gasoline floats on water. Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day. Large volumes may penetrate soil and could contaminate groundwater. Ethanol and methanol are soluble in water.

12.5 PBT & vPvB ASSESSMENT:

The product does not contain substances assessed to be PBT or vPvB.

12.6 OTHER ADVERSE EFFECTS:

Films formed on water may affect oxygen transfer and damage organisms.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS:

WASTE DISPOSAL

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor to deal satisfactorily with this type of product should be established beforehand. Do not dispose into the environment, in drains or in watercourses. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.

PRODUCT DISPOSAL

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

European Waste Code: 13 07 02 petrol

NOTE: This code has been assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste generators/producers are responsible for assessing the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code.

PACKAGING DISPOSAL

Waste packaging should be recycled wherever possible. Send to drum recycler or metal reclaimer. Care should be taken when handling emptied containers that have not been cleaned out. Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Residues may cause an explosion hazard if heated above the flash point. Do not puncture, cut or weld uncleaned drums. Do not pollute the soil, water or environment with the waste container. Comply with any local recovery or waste disposal regulations. Incineration or landfill should only be considered when recycling is not feasible.

LOCAL LEGISLATION:

Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with Hazardous Waste (England and Wales) Regulations 2005



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

SECTION 14. TRANSPORT INFORMATION

14.1 UN NUMBER

1203

14.2 UN PROPER SHIPPING NAME

PETROL

14.3 TRANSPORT HAZARD CLASS(ES)

3

14.4 PACKING GROUP

II

14.5 ENVIRONMENTAL HAZARDS

ADR/IATA/RID/ADN YES
IMDG: Marine Pollutant: YES

14.6 SPECIAL PRECAUTIONS FOR THE USER

Read SDS and supplier instructions on correct use of the product.

Transport Category: 2
Tunnel Restriction Code: (D/E)
Emergency Action Code: 3YE

14.7 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

The product is not intended to be transported in bulk. MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15. REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

This Safety Data Sheet was prepared in accordance with EC Regulation (EC) No. 1907/2006 as amended. The product has been classified in accordance with Regulation (EC) No. 1272/2008 (CLP).

15.2 CHEMICAL SAFETY ASSESSMENT

A chemical safety assessment has not been carried out.

SECTION 16. OTHER INFORMATION

HISTORY:

Version 01 ISSUED 06/08/2019, first release



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

REFERENCES:

Concawe Report 01/97 – Petroleum Products – First Aid Emergency and Medical Advice.
Concawe Report 00/56 – Revised Preparations – Summary Data and Rationale.
CENELEC CLC/TR 50404 Electrostatics – Code of Practice for the Avoidance of Hazards Due to Static Electricity.
Dangerous Goods Regulations – ADR/RID, ADN/ADNR, IMDG, IATA.
European Model Code of Safe Practice in the Storage and Handling of Petroleum Products, Associated Octel Company.
UK – Leaded Gasoline Tank Cleaning and Disposal of Sludge (Booklet OIP/5 (5/99)).
ECHA REACH Dossier

ABBREVIATIONS:

ACGIH	American Conference of Governmental Industrial Hygienists.
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS number	Chemical Abstracts Service Number
CLP	Classification, Labelling and Packaging
EC number	European Inventory of Existing Commercial Chemical Substances or European List of Notified Chemical Substances number
EC50	Effective Concentration 50%
EL50	Effective Loading 50%
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal does
LL50	Lethal Loading 50%
LOAEL	Lowest observed adverse effect level
NOAEL	No observed adverse effect level
NOEL	No observed effect level
PBT	persistent, bioaccumulative and toxic
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
STOT	Specific target organ toxicity
TWA	Time-Weighted Average
UVCB	substance of unknown or variable composition, complex reaction products or biological materials
vPvB	very persistent and very bioaccumulative
WAF	Water Accommodated Fraction

FULL TEXT OF HAZARD STATEMENTS AND HAZARD CODES:

Flam. Liq. 1 or 2	Flammable liquids, Hazard Categories 1 or 2
Asp. Tox. 1	Aspiration hazard, Hazard Category 1
Skin Irrit. 2	Skin corrosion/irritation, Hazard Category 2
Acute Tox. 3	Acute Toxicity, Hazard Category 3
Muta. 1B	Germ cell mutagenicity, Hazard Category 1B
Carc. 1B	Carcinogenicity, Hazard Category 1B
Repr. 2	Reproductive toxicity, Hazard Category 2
STOT SE 3	Specific Target Organ Toxicity – Single Exposure, Hazard Category 3
STOT RE 1 or 2	Specific Target Organ Toxicity – Repeated Exposure, Hazard Category 1 or 2
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic, Hazard Category 2
H224	Extremely flammable liquid and vapour.



SAFETY DATA SHEET

ULP

According to Regulation (EC) No. 1907/2006 as amended

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin
H315	Causes skin irritation.
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H350	May cause cancer.
H361df	Suspected of damaging fertility. Suspected of damaging the unborn child
H370	Causes damage to organs (Optic nerve, central nervous system)
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long-lasting effects

SDS DISTRIBUTION AND TRAINING

This document contains important information to ensure the safe storage, handling and use of this product. The information in this document should be brought to the attention of the person in your organisation responsible for advising on safety matters. Workers should be trained to handle this substance safely.

FURTHER INFORMATION:

Users are advised to refer to relevant legislation, approved codes of practice and guidance available from the Health & Safety Executive (website: <http://www.hse.gov.uk>) and to the IP Codes of Practice available from the Energy Institute (website: <http://www.energyinst.org.uk>)

DISCLAIMER:

The above information is based on our current knowledge of the product. The purpose of this data sheet is to describe the product in terms of its safety and environmental requirements. It is the user's responsibility to satisfy themselves as to the application of this information and/or recommendations for their own use. This safety data sheet contains important information to ensure the safe storage, handling and use of this product, it does not however constitute an assessment of workplace risks. The advice given in this safety data sheet reflects the current knowledge of the hazards and risks associated with the handling of the product. If the product is mixed with other materials the users shall take these into account in identifying any additional hazards and risks might arise.